



Protocol/Manufacturer

BACnet (IP/Ethernet/MSTP)
KNX (EIBNet/IP)
EIB
Modbus (RTU, ASCII, TCP)
LON
Danbuss
Exoline
SAIA
SIOX
Mbus
Staefa NICO
Staefa NITEL
Trend
Omron
KTC / SRDLink
Cylon
Comli
Carel
INU
Johnson/N2
Smartbox
Mercury
EnGuard
ALCO
EMU
Honeywell/ELM
Unisab
Frick
Metasys
Excom
SNMP
ISN
Brunata
Bewator
Netavent
Davis

Utility drivers

Calculus
Watcher
Simulation
T-Pipe

Transport drivers

Serial
IP
Modem

Example hardware

YORK CX-AHU-BLRS, CX-TC L, Kieback & Peter DDC 4200, Loytec LVIS
KNX devices through IP-routers Siemens N-146, Hensel EMS 0207, Merten.
EIB devices through FT 1.2 PEI Type 10 compatible serial interfaces (BCU2)
Carlo Gavazzi Mastergenerator, WM22, Elcontrol SIRIO, Staetriconic 700
Regin EP8210, SysMik, LK NETLON, York FX16, YKLON
AKA243B gateway connected to an AKL111A.
All Regin products. Exomatic ASM, EXOflex, EXOcompact, Corrigo
PCD1 (S-bus data mode), PCD2 (S-bus data mode UDP).
R02, R03, S45 through K32 serial converter.
Brunata energy meter HGQ.
Staefa NICO
Staefa NITEL
IQ220, IQ3
CJ1M CPU11.
KTC SRD3100.
UCC4, UC16.
Alliance ADU 200.
MPX master and pCO2 through Carel Pcgate.
INU Control, PSR2000.
Johnson Controls DX91xx, DC91xx, DR91xx.
Smartbox.
Mercury 6-5E through a Mercury IP network module (PR0016).
RC-02 90016 ISSUE 2.
Emerson EC3-332.
TVC
ELM
Unisab compressors through RS2LAN and COMSAB.
Frick Quantum LX Panel.
Johnson Controls DX9100, misc METASYS controllers.
Staetriconic 700.
Emerson Alco EC3-332, EC2-312.
ISN IDC through Linc.
BrunataNet Boxlan, Json.
Access controll and card readers.
Ventilation solutions.
Weather systems.

Example usage

Perform simple calculus such as averaging, sums etc.
Monitor external hardware through ping etc.
Generate simulated data.
Connect third party software or hardware through Greyhound driver stack.

Example medium

RS232, RS422, RS485, USB<->Serial
TCP, UDP
Modem

Not all drivers available to general public.

All drivers developed in cooperation with the manufacturer.

For the latest version please visit www.botech.se.

All registered trademarks are used for identifying purposes only.

